

Specifications		8-NC	3N	10N	10NW	10AII	10AIIW	KS-6N
Max.diameter of gear	DP	12	34	10	10	10	10	25
Max.diameter of gear	inch	6.299	1.181	3.937	3.937	3.937	3.937	2.362
Number of teeth	Z	3 ~ 999	3 ~ 999	3 ~ 999	3 ~ 999	5 ~ 100	5 ~ 100	Number of cutter strokes
Swivel angle of hob head	°	+160 ~ -20	±45	±45	+117 ~ -45	±45	±45	
Max.hob spindle speeds	rpm	3,000	6,000	4,000	4,000	1,500	1,500	
Floor sspace	inch	47.83×57.48	54.29×54.17	66.14×68.90	66.14×68.90	60.83×50.20	69.09×53.15	39.37×53.94
Net weight	lb	3,086	3,086	7,936	7,936	4,630	4,630	4,409
Kind of gears to be cut								
Spur gear		OK	OK	OK	OK	OK	OK	OK
Helical gear		OK	OK	OK	OK	OK	OK	NG
Worm wheel		OK	OK	OK	OK	OK	OK	NG
Worm		OK	NG	NG	OK	NG	NG	NG
Internal gear		NG	NG	NG	NG	NG	NG	OK
Stepped gear		NG	NG	NG	NG	NG	NG	OK